Project Name: _		_ AIA#:	
Model #:	Location:		

Cilobe

SIS#:

# 5 Quart **Countertop Mixer**

Built into each mixer is the quality of workmanship and design synonymous with Globe.

### Model

SP5 - 5 Quart Power Mixer Color-White with gray top







Quantity:

#### Standard Features

- Heavy-duty motor, 800 watts
- Gear-driven, high torque transmission and motor
- Ten speeds
- Electronic speed and load control
- · Durable, NSF approved, white powder coating
- Rigid cast aluminum body
- Polycarbonate splash cover with ingredient chute
- All stainless steel attachments
- Dual bowl clamps to lock bowl down
- Permanently lubricated transmission

- · Thermal overload protection
- Attachment hub
- · Easy action bowl lift
- #10 Attachement hub
- Six foot cord with plug

#### Standard Accessories:

- 5 quart polished stainless steel bowl
- · Stainless steel flat beater
- · Stainless steel wire whip
- Stainless steel spiral dough hook
- Polycarbonate splash cover

### Warranty

Two-year parts and one-year labor

_		4				
n	n	м	$\mathbf{n}$	n	а	•
u	ш	ш	ıu		а	


- ☐ Mixer table with undershelf
- ☐ Extended Warrantv


(More options on back)

approved by:	Date:	
''		

# **5 Quart Countertop Mixer**

#### SP<sub>5</sub>





Drawings available through KCL. www.kclcad.com

Model	Elevation	Right	Plan	Back	BIM 3D	Revit
SP5						

SPECIFICATIONS																	
Model	Motor	Volts	Amps	Transmission Type	Capacity	0	1	2	3	Agita	tor Spe 5	eds (RF 6	Ms) 7	8	9	10	Attachment Speeds (RPMs)
SP5	800 W	115/60/1	4	Gear	5 qt / 5 L	OFF	30	50	70	90	105	120	145	165	180	200	50 to 450

Cord & Plug: Attached 6 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15P (1)

#### FEATURES:

**Transmission:** Heavy duty transmission with precision milled gears operate the planetary action and provide high torque mixing power. Gears are packed in a long lasting grease, and all shafts are mounted in ball bearings.

## Electronic Speed and Load Control:

Guarantees consistent kneading and mixing performance.

#### Manual Reset:

Electrically controlled thermal overload protection.

#### STANDARD ACCESSORIES:

- 5 Quart #304 series stainless steel bowl
- Stainless steel dough hook, beater, and wire whip
- Polycarbonate splash cover with built-in ingredient chute
- Spatula

#### **OPTIONAL ACCESSORY:**

• XXTABLE - Mixer Table with undershelf (Stainless steel top with galvanized steel undershelf and legs.) 30" W x 24" D x 24" H (76.2cm x 61cm x 61cm)

#### **EXTENDED WARRANTY**

 SP-XD58 Extended warranty for the SP5 mixer. Coverage extends factory warranty to 2-years. Only available at time of purchase. (U.S.A. Only)

DIMENSIO	ONS & SHIPPING INFOR	RMATION			Freight Class 85						
Cartons are reinforced for shipping. The weight and dimensions of this reinforced carton are included below and may vary from shipment to											
Model	Foot Print	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight						
SP5	13.1" D x 15.3" W (33.4 cm x 38.9 cm)	15.3" L x 13.1" W x 17.1" H (38.9 cm x 33.4 cm x 43.3 cm)	33 lbs. (15 kg)	18.5" L x 15" W x 21.5" H (46 cm x 37 cm x 52 cm)	40 lbs. (18 kg)						

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodequip.com